BUROCCO
INOXVALVOLE
PATENTED PNEUMATIC VALVES

Pos. 1

Code	**H1AE93TM5NHBE7C2A6O**
Description	VR S3000 - 1/2" (DN15) - PN40 - CV 1H - AISI 316L - FF - GAS - (MET CL VI) - OTT SP EQP - TRIM 17-4PH - PTFE-LTS+OR - BG.PTFE - SERV. S200/I - AZ AA - CM 3/15 PSI - C.20MM - T -30/+180°C

ARTICLE TYPE	H	SERIE 3000
BODY SHAPE	1	2 WAY GLOBE
SIZE	A	DN 15 (1/2”)
RATING	E	PN 40
CV DN 15	9	CV 1H
BODY / CONNECTIONS MATERIAL	3	AISI 316L
END CONNECTIONS	T	THREAD FEMALE
CONNECTION CHARACTERISTIC	M	THREAD GAS
SEAT-PLUG SEAL	5	CLASS VI (metallic)
PLUG TYPE	N	NEEDLE EQ%
PLUG - SEAT MATERIAL	H	17-4 PH
BODY GASKETS - STEM SEALING	B	PTFE - PTFE+OR(FPM)
BONNET - GUIDE BUSHING	E	STANDARD - PTFE
YOKE TYPE	7	TYPE 1000/3000/4000 ON COLUMNS IN STAINLESS STEEL
SERVOCONTROL TYPE	C	S.200
ACTION	2	N.C. REVERSE (normally closed straight way)
SPRINGS TYPE	A	0.2 - 1 bar (3-15 psi)
STROKE	6	20 mm
MEDIUM MINIMUM - MAXIMUM TEMPERATURE	O	-30/+180°C

cod. APOSIFA4-SM1- ELECTRO-PNEUMATIC POSITIONER SMC MOD. IP8000 COMPLETE GAUGE, INPUT 4-20 MA, PROTECTION IP65. (INSTRUMENT PLACED PIPING IN PLASTIC AND FITTING IN BRASS)

ΔP_{max} 40 bar

CERTIFIED QUALITY MANAGEMENT SYSTEM ISO 9001:2008 SINCERT DNV